



CILINDRO SEMPLICE EFFETTO TUFFANTE SERIE M250 - SINGLE ACTING CYLINDER M250 SERIES - PLUNGER CYLINDER SERIE M250

HFRT **M250**

Ø D	Ø AL	Ø S	Corsa Stroke Hub	Codice Code Bestell-Nr.	K	E	M	C	L1	Ø F Ø F1	Ø G	ØH1	Kg	Euro
40	30	25	100	HFRT125100	190	3/8"	35	38	40	14	22	40	1,63	65,30
			150	HFRT125150	240								2,04	68,95
			200	HFRT125200	290								2,44	72,60
			250	HFRT125250	340								2,85	76,25
			300	HFRT125300	390								3,26	79,90
50	40	30	200	HFRT230200	300	3/8"	37	42	42	16	27	50	3,61	87,55
			250	HFRT230250	350								4,16	92,30
			300	HFRT230300	400								4,72	97,05
			350	HFRT230350	450								5,27	101,80
			400	HFRT230400	500								5,82	106,55
			550	HFRT230550	650								7,30	120,75
60	50	40	200	HFRT340200	330	3/8"	49	54	47	23	37	60	6,00	117,70
			250	HFRT340250	380								6,84	124,60
			300	HFRT340300	430								7,67	131,50
			350	HFRT340350	480								8,49	138,40
			400	HFRT340400	530								9,32	145,30
			550	HFRT340550	680								11,70	166,00
			700	HFRT340700	830								14,10	186,70
70	60	50	300	HFRT450300	460	3/8"	65	74	50	25,5	47	65	11,80	173,60
			400	HFRT450400	560								14,00	192,85
			550	HFRT450550	710								17,50	221,75
			700	HFRT450700	860								21,00	250,65

MATERIALE - MATERIAL:

TUBO - TUBE - ROHR: ACCIAIO - STEEL - STAHL ST52,3 DIN2393 ISO H9

STELO - ROD - KOLBENSTANGE: ACCIAIO - STEEL - STAHL UNI C45 CROMO - CHROME - CHROM: 25 MICRON ± 5



Velocità Limite - Top Speed -
Höchstgeschwindigkeit: max. 0,5 m/s
Pressione Continua - Continuous Pressure -
Dauerdruck: max. 140 bar
Pressione di picco - Peak pressure -
Höchstdruck: max. 250 bar
Temperatura C° - Temperature C° -
Temperaturbereich C°: -25°C +80°C